SOLVENT SUPPLIES LTD

33 Miro Street Otaki NZ Website: www.solventsupplies.co.nz Email: support@solventsupplies.co.nz

Issue: April 2024

	Section 1:	Identification of the Material and Supplier
--	------------	---

Product Name:	Methanol
Other Names:	Methyl alcohol, methyl hydroxide, carbinol, pyroxylic
	acid, wood alcohol, wood naphtha, wood spirit.
Recommended use: Solvent, fuel, feedstock	
Company Name: Solvent Supplies Limited	
Address:	33 Miro Street
	Otaki
	New Zealand
Email:	support@solventsupplies.co.nz
Emergency Telephone:	New Zealand Poisons Centre: 0800 764 766
	Fire, Police, Ambulance: 111

Section 2:	Hazards Identification	
------------	------------------------	--

Hazardous substance according to the HSNO Act 1996 Hazardous Substances (Classification) Notice 2017.

EPA New Zealand Approval Code: HSR001186

Refer to www.epa.govt.nz for Controls for this substance. **HSNO Hazard Classification:** 3.1B, 6.1C, 6.4A, 6.8B, 6.9A, 9.3C

Pictograms:









Signal Word: DANGER

Hazardous Statements

H225 Highly Flammable liquid and vapour.	H372 Causes damage to organs through repeated or
11223 Highly Hammable liquid and vapour.	prolonged exposure.
H301 Toxic if swallowed.	H411 Toxic to aquatic life with long lasting effects.
H311 Toxic in contact with skin.	H433 Harmful to terrestrial vertebrates
H319 Causes serious eye irritation.	
H331 Toxic if inhaled.	
H361 Suspected of damaging fertility or	
the unborn child.	

Methanol ©Solvent Supplies Ltd

Prevention Statements

P102 Keep out of reach of children. P201 Obtain special instructions before use. P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment. P242 Use non-sparking tools	- 101011110		
P202 Do not handle until all safety precautions have been read and understood. P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment.	P102	Keep out of reach of children.	
P210 Keep away from heat/sparks/open flames/hot surfaces. No smoking. P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment.	P201	Obtain special instructions before use.	
P233 Keep container tightly closed. P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment.	P202	Do not handle until all safety precautions have been read and understood.	
P240 Ground/bond container and receiving equipment. P241 Use explosion-proof electrical/ventilating/lighting equipment.	P210	Keep away from heat/sparks/open flames/hot surfaces. No smoking.	
P241 Use explosion-proof electrical/ventilating/lighting equipment.	P233	Keep container tightly closed.	
	P240	Ground/bond container and receiving equipment.	
P242 Use non-sparking tools	P241	Use explosion-proof electrical/ventilating/lighting equipment.	
12.12 Ose non sparking tools.	P242	Use non-sparking tools.	
P243 Take precautionary measures against static discharge.	P243	Take precautionary measures against static discharge.	
P260 Do not breathe vapours.	P260	Do not breathe vapours.	
P264 Wash hands thoroughly after handling.	P264	Wash hands thoroughly after handling.	
P270 Do not eat, drink or smoke when using this product.	P270	Do not eat, drink or smoke when using this product.	
P271 Use only outdoors or in a well ventilated area.	P271	Use only outdoors or in a well ventilated area.	
P273 Avoid release to the environment.	P273	Avoid release to the environment.	
P280 Wear protective gloves and protective eye/face protection.	P280	Wear protective gloves and protective eye/face protection.	
P281 Use personal protection equipment as required.	P281	Use personal protection equipment as required.	

Response Statements

response statements	-
P308+P313	If exposed or concerned get medical advice.
P314	Get medical advice if you feel unwell.
P301+P310	If swallowed immediately call a Poison Centre or doctor.
P330	Rinse Mouth.
P302+P352	If on skin wash with plenty of soap and water.
P312	Call a Poison Centre or Doctor if you feel unwell.
P361	Take off immediately all contaminated clothing.
P363	Wash contaminated clothing before reuse.
P303+P361+P353	If on skin or hair: Remove immediately all contaminated clothing. Rinse skin
	with water.
P304+P340	If inhaled remove to fresh air and keep at rest in a position comfortable for
	breathing.
P311	Call a Poison Centre or Doctor.
P305+P351+P338	If in eyes, rinse cautiously with water for several minutes. Remove contact
	lenses if present and easy to do so. Continue rinsing.
P337+P313	If eye irritation persists get medical advice.
P370+P378	In case of fire use water fog or mist or alcohol-resistant foam.

Storage Statement

P403+P235	Store in well-ventilated place. Keep container tightly closed. Keep cool.
P405	Store locked up.

Disposal Statement

Methanol ©Solvent Supplies Ltd

P501	Dispose of product to a landfill in accordance with any local regulations.
------	--

Section 3:	Composition/Information on Ingredients
------------	--

Common Name:	CAS No:	Proportion (% v/v)
Methanol	67-56-1	100

Section 4:	First Aid Measures

Consult the NATIONAL POISON CENTRE (NZ 0800 764 766) or doctor in every case of suspected poisoning, or if exposed and concerned. If medical advice is needed, have product container or label at hand.

Ingestion:	Rinse mouth with water. DO NOT induce vomiting. Immediately call a Poison Centre or
	doctor for advice. Do NOT delay. Ingestion of methanol is potentially life threatening. If
	vomiting occurs spontaneously, keep head below hips to prevent aspiration.
Inhalation: Move person to fresh air immediately. Keep warm and at rest until reco	
	Poison Centre or Doctor immediately for advice. If breathing is difficult, administer
	oxygen.
Skin:	Remove all contaminated clothing and footwear immediately. Wash affected area with
	plenty of water followed by soap and water. If irritation persists, get medical advice.
Eyes:	Hold eyes open and rinse cautiously with water for several minutes. Remove contact
	lenses if present and easy to do so after the first 5 minutes. Continue rinsing for at least
	15 minutes. Get medical attention if irritation persists.
Advice to Treat symptomatically. Acute exposure to methanol either through in	
Physician:	inhalation of high concentrations can result in symptoms appearing between 40 minutes
	and 72 hours following exposure. Symptoms/signs are usually limited to the central
	nervous system (CNS), eyes and gastrointestinal tract. Initial CNS effects (headache,
	vertigo, lethargy, confusion) may give the impression of ethanol intoxication. Blurred
	vision, decreased acuity (ability to see, hear and understand) and photophobia (visual
	intolerance to light) are also common. Treatment with IPECAC or lavage is indicated for
	any patient presenting within two hours of ingestion. A profound metabolic acidosis
	occurs in severe poisoning and serum bicarbonate levels are a more accurate of severity
	than the serum methanol levels. Ethanol significantly decreases the toxicity of methanol
	because it competes for the same metabolic enzymes.

Section 5:	Fire Fighting Measures
------------	------------------------

Extinguishing Media:	Use dry chemical powder, carbon dioxide or water spray or alcohol resistant foam. For large fires use alcohol resistant foam. DO NOT use water in a jet.
Fire & Explosion Hazards:	Methanol vapours may burn with an invisible or clear flame.
	Toxic gases and vapours may be generated; carbon monoxide,

Methanol ©Solvent Supplies Ltd

	carbon dioxide, formaldehyde.
Specific Hazards:	Vapours can accumulate in confined spaces resulting in toxicity and flammability hazards. Vapours can flow along surfaces to distant ignition sources and flash back. Closed containers may rupture violently and suddenly release large quantities of product. Cool fire exposed containers with water spray. Concentrations of >25% methanol in water can be ignited.
Fire-fighting Equipment:	Wear self-contained breathing apparatus and personal
	protection clothing.

Section 6:	Accidental Release Measures	
------------	-----------------------------	--

Spills:

Highly flammable liquid. Can burn without visible flame. Vapour forms explosive mixture with air. Isolate hazard area and keep unnecessary or unprotected people away from area. Stay upwind and keep out of low lying areas. Wear personal protective equipment. Avoid contact with skin and eyes. Shut off leak if safe to do so. Remove or isolate ignition sources. Contain spill. Avoid run off into drains or sewers. Do not contaminate watercourses or the ground. Take precautions against static discharge. Bound or ground (earth) all equipment. Ventilate contaminated area.

For large spills (more than a drum) recover liquid and transfer by mechanical means to labeled salvage tank that can be sealed for recovery or disposal of product. Allow residues to evaporate. Water can be used to disperse vapours and to clean spill area and dispose of safety by waste management company. For small spills absorb with an appropriate material e.g. vermiculite, and dispose of waste safely in a labeled sealed container for recovery or disposal.

If contamination of drains, sewers or water ways occurs, immediately notify Emergency Services (111).

Disposal:

Dispose of contaminated waste or product to a solvent recycling facility or to an approved landfill in accordance to local regulations.

Section 7:	Handling and Storage

Handling:

Highly flammable liquid. Read label before use. Use only in well-ventilated area. Avoid breathing vapours or direct contact with product. Wear personal protection equipment. Wash hands and exposed skin after handling. Wash contaminated clothing and equipment before reuse.

No smoking. Remove or isolate ignition sources. Avoid sparks. Electrostatic charge may be generated during pumping with risk of fire. Restrict line viscosity to avoid generation of electrostatic discharge.

Take precautions to use bonded or grounded (earthed) equipment. Do not use compressed air for filling, discharging or handling. Keep container closed when not in use. Wear personal protective equipment to prevent breathing of and contact with product. Wear gloves and protect eyes from splashes. Wash hands and exposed skin after handling.

Storage:

Methanol ©Solvent Supplies Ltd

Ensure all storage areas have adequate fire-fighting equipment. Store locked up in original container in a secure cool dry well ventilated place, away from sunlight, ignition sources, heat, incompatible substances, aerosols, other flammables, oxidizing agents and corrosives, out of reach of children and away from food, drink and animal foodstuffs. Take precautions to avoid accumulation of vapours in pits and confined spaces. All equipment must be grounded/bonded when transferring product to avoid static discharge. Ensure all ignition sources are eliminated or purge storage tanks with inert gas such as nitrogen.

Recommended materials:

Anhydrous methanol is non-corrosive to most metals at ambient temperatures except for lead, nickel, monel, cast iron and high silicon iron. Polyethylene, neoprene, phenolic resins, polyesters, natural rubber, butyl rubber and polyvinyl chloride (unplasticised) shown more resistance to corrosion by methanol.

Unsuitable materials:

Coatings of copper (or copper alloys), zinc (including galvanized steel) or aluminum are unsuitable for storage. May attack some forms of plastic, rubber and coatings.

Section 8:	Exposure Controls/Personal Protection
0000.01.01	

Exposure Guidelines:

NZ Workplace Exposure Standard (WES) has been set for this substance.

	WES-TWA	WES-STEL
Methanol вю. sкin	200 ppm (262 mg/m ₃)	250 ppm (262 mg/m ₃)

Engineering Controls:

Use only in a well ventilated area. An approved half-face filter mask may be suitable for low concentration level exposures. Otherwise, use an appropriate full-face mask fitted with an approved vapour cartridge. Where air filtering respirators are unsuitable (e.g. airborne concentrations are high, risk or oxygen deficiency, confined space) use positive pressure breathing apparatus.

Personal Protection Equipment (PPE):

Wear protective clothing and safety boots or shoes. Wear appropriate chemical resistant gloves e.g. butyl or nitrile rubber. Wear chemical goggles or safety glasses with side shields.

|--|

Appearance:	Clear, colourless liquid
Odour:	Mild, characteristic alcohol
Odour Threshold:	Not available

Methanol ©Solvent Supplies Ltd

pH:		Not applicable
Melting Point/Freezing Point	°C	Not applicable
Boiling Point/Boiling Range:	°C	64.7
Freezing Point	°C	Not available
Flash Point:	°C	11.0
Flammability:	(solid, gas)	Not applicable
Upper/Lower Flammability limits in air	(% v/v):	6.0 to 36.5
Vapour Pressure:	kPa @ 20°C	12
Vapour Density:	(air=1)	1.105 @ 15°C
Relative Density at 15°C:	g/cc	0.82
Solubility in water:		Completely soluble
Partition coefficient:	n-octanol/water	Not available
Auto Ignition Temperature:	°C	464
Decomposition Temperature:	°C	Not available
Kinematic Viscosity:		Not available
Volatile Organic Carbon Content:		Not available
Evaporation Rate:	(nBuAc =1)	4.1

Section 10:	Stability and Activity	
-------------	------------------------	--

Stability:	Stable under normal conditions of storage and use.
Conditions to avoid:	Avoid heat, sparks, open flames and other ignition sources.
Incompatibility (Materials to avoid):	Strong oxidizing agents, strong mineral or organic acids and strong bases. Contact may result in a violent or explosive reaction. Corrosive to lead, aluminum or magnesium and platinum. May react with metallic aluminum or magnesium and generate hydrogen gas. May attack some forms of plastic, rubber and coatings.
Hazardous Decomposition Product:	Dependent on conditions under which decomposition occurs; gases (carbon monoxide, carbon dioxide, formaldehyde) will be evolved.
Hazardous Polymerization:	Not known to occur.

Section 11:	Toxicological Information	
-------------	---------------------------	--

Potential Health Effects:

This section includes possible adverse effects which might occur if this product is not handled in the recommended manner.

Acute Toxicity:	Toxic if ingested and absorbed through skin or by inhalation. Ingestion of
	even small amounts could potentially cause blindness and death. Odour

Methanol ©Solvent Supplies Ltd

	threshold is several times higher than WES concentration. Symptoms/signs	
	are usually limited to the central nervous system (CNS), eyes and	
	gastrointestinal tract. Effects of sub lethal doses can be nausea, headache,	
	abdominal pain, vomiting and visual disturbances. Initial CNS effects	
	(headache, vertigo, lethargy, confusion) may give the impression of ethanol	
	intoxication. Blurred vision, decreased acuity (ability to see, hear and	
	understand) and photophobia (visual intolerance to light) are common.	
Aspiration Hazard:	Not classified.	
Respiratory Irritation:	May irritate the upper respiratory tract.	
Skin Corrosion/Irritation:	Prolonged contact may also result in defatting of the skin leading to	
	dermatitis and aggravation of any pre-existing skin conditions.	
Serious Eye	Mild to moderate irritant to eyes. Symptoms can include tearing, redness	
Damage/Irritation:	and blurring.	
Respiratory or Skin	Not classified for sensitization effects.	
Sensitization:		
Germ Cell Mutagenicity:	Not classified with mutagenic properties.	
Carcinogenicity:	Not classified with carcinogenic properties.	
Reproductive Toxicity:	Not classified.	
Specific Organ Toxicity	Causes visual disturbances e.g. blurring or vision, constriction of visible field	
(Repeated and Single	in colour perception, temporary or permanent blindness.	
Exposure):		
Narcotic Effects:	Vapours are inhaled at high concentrations will have effects on central	
	nervous system; nausea, dizziness, drowsiness.	

Toxicological Information:

Human, Oral:	LD ₅₀	300 mg/kg bw
Human:	LC50 (4h)	10 mg/L

Primates have dermal LD_{50} OF 393 mg/kg; monkey has inhalation of LC_{50} (4h) of 52 mg/L. Humans are considered to be 6 to 10 times more susceptible.

Additional Information:

Persons with pre-existing skin disorders, eye problems, respiratory conditions or impaired liver or kidney functions may be more susceptible to the effects of this product.

Section 12:	Hazard Identification	

Eco-Toxicity:	Product is classified as harmful to terrestrial vertebrates.
Persistence/Degradability:	Expected to be rapidly biodegradable. Readily evaporates. Oxidizes by
	photochemical reactions in air.
Potential for Bioaccumulation:	Not expected to bio-accumulate significantly.
Mobility in soil:	Soluble in water. Expected to have high mobility in soil.
Other adverse effects:	Not available
Ecological Data:	Methanol: Mouse, Oral, LD50 870 mg/kg bw

Methanol ©Solvent Supplies Ltd

Section 13:

Disposal Considerations

Disposal:

Recover and recycle product whenever possible. Send clean, dry drums to recycling facility or metal scrap re-claimer. Dispose of waste in accordance with Regional Authority or local council bylaws.

Special Precautions:

Ensure empty containers are vented and dry. Residues may cause an explosion hazard. Do not puncture, cut or weld unclean drums. Do not use empty drums for storing other products.

Section 14: Transport Information

This product is classified as a Dangerous Goods Class 3, packing group II.

Please consult the Land Transport Rule: Dangerous Goods 2005 and NZS 5433:2012 Transport of Dangerous Goods on Land for information.

Transport Information

UN Number:	1230
Proper Shipping Name:	METHANOL
Class:	3
Sub risk:	6.1
Packing Group:	II
HAZCHEM:	3WE
Marine Pollutant:	No



Section 15: Regulatory Information

Hazardous substance according to the HSNO Act 1996 Hazardous Substances (Classification) Notice 2017.

HSNO Substance Approval Code: HSR001186; Methanol

Refer to Section 2 for hazardous classification and to www.epa.govt.nz for controls and conditions. For additional compliance information, refer to Worksafe NZ www.worksafe.govt.nz

Section 16: Other Information

Date of Preparation: April 2024.

Replaces: SDS Dated March 2019.

Methanol ©Solvent Supplies Ltd

Reasons for Issue: Review of SDS and product information.

Abbreviations:

CAS Number: Chemical Abstracts Number

EPA: Environmental Protection Authority **HSNO:** Hazardous Substances & New Organisms

STEL: Short Term Exposure Limit (15 minute exposure period)

TWA: Time Weighted Average
WES: Workplace Exposure Standard

Safety data sheets are updated frequently. Please ensure you have a current copy.

Disclaimer:

Before using this product, read its label carefully to ensure that you understand its contents. The information contained herein is based on data considered accurate and reliable to the best of our knowledge and belief of the date complied. However no warranty is expressed or implied regarding the accuracy of this data or the results to be obtained from the use hereof. Solvent Supplies Limited assumes no responsibility for personal injury or property damage to vendors, users or third parties caused by the material. Such users or vendor assume all risks associated with the use of the material. It is the user's responsibility to satisfy themselves as to the suitability and completeness of the information for their own particular use. The users must determine whether the use of the information and data is in accordance with local laws and regulations

Methanol ©Solvent Supplies Ltd

Date: April 2024

Review: March 2029 Page 9